




Bird series Bird Pro series





The Bird generation with brushless motor – reliability for a high run and fast work sequence.





PowerBird® Pro





PowerBird® Pro

Gold Edition with
spring-loaded trigger system

THE NEXT GENERATION OF BATTERY-POWERED BLIND RIVET TECHNOLOGY

60 years experience, 60 years expertise. Fast and powerful as never before: the **Bird Pro series**.

The Bird Pro series

GESIPA®, who invented battery-powered blind riveting technology, has been producing the Bird series for over twenty years now. To this day, it sets the standard for the battery-powered blind riveting devices market. Not least, due to changing customer requirements, the Bird

family's modular system is updated on a regular basis. GESIPA® has therefore built a new platform that supplement the current Bird series to meet the highest customer requirements.

Special features

1 Auto reverse function

Immediately after mandrel break-off, this optional operating mode stops the pulling process and moves the jaw assembly back into the initial position. This saves time and energy while making sure the tool is immediately ready for use.

2 Lighting

The light-emitting diodes precisely aligned to the work piece are integrated into the adjusting ring. There are three possible switch positions:

Process controlled: The diodes remain illuminated after the setting process, which allows a continuous workflow even under bad lighting conditions

Torch function: Steady glow of diode for max. 10 minutes

Lighting off: Saves electricity

3 Sliding battery

New sliding battery with exact optical and acoustic charging status display prevents unpleasant surprises. The deep sleep function and the electrical feedback of the braking energy extend the battery range – a battery charge lasts for up to 2,000 riveting operations. Additional catching grids prevent falling.

4 Charging unit

Charging unit with quick-charge function. The battery can be used again after only 45 minutes of charging, and is fully charged after just 90 minutes.









_



ADVANTAGES OF THE BIRD PRO SERIES

High efficiency, long service life, particularly smooth running

BLDC technology

A BLDC motor is a brushless DC motor that, instead of brushes that are susceptible to wear, uses electrical sensors to detect the rotor's position and commutate the stator coil via circuit breakers. A special software in the electronics controls the motor.

The advantages of a BLDC motor include high efficiency, long service life, particulary smooth running with a precision ball bearing and a reduction in electrical noise radiation.



Li-ion battery

The GESIPA® Bird Pro series is equipped as standard with a new rechargeable 2.1 Ah Li-ion slide-on battery. These rechargeable Li-ion batteries feature the Deep Sleep function. To keep intrinsic consumption as low as possible, after a set idle time, the battery automatically assumes "Deep Sleep" mode. By turning on the device the battery is automatically woken and is immediately ready for use.

Charging technology

The GESIPA® Li-ion chargers are available for 110 V to 240 V AC voltages. The charger comes with a Euro plug as standard. Other versions for China, UK and USA are available on request.

Advantages at a glace

- More powerful and longer-lasting **BLDC** motor for quick flow of work
- 25 mm stroke for long blind rivets
 Up to 20 kN setting force for particularly large blind rivets
- Variable lighting in the adjusting ring
 Increased stability due to larger, non-slip stand surface and lower center of gravity
- Easy-to-grasp housing thanks to Softgrip
- New sliding battery

- Charging unit with quick-charge function
- Shortened pulling process thanks to the auto reverse function for quicker flow of
- Well proven and virtually no wear: the patented jaw system provides a very long service life and helps saving spare part costs
- Ergonomical design: rubberised, moulded grip and a balanced center of gravity

BATTERY-POWERED BLIND RIVET SETTING TOOLS WITH BRUSHLESS **MOTOR**



AccuBird® Pro

The fast one

- up to 4x faster than other battery-powered tools on the market!

The brushless motor and 10,000 N setting force make the AccuBird® Pro extremely fast for setting blind rivets of any material up to \varnothing 5 mm.

PowerBird® Pro

The all-rounder

- exceptional speed and high power!

With a setting force of 15,000 N and the well-proven brushless motor, the PowerBird® Pro is powerful and fast when setting blind rivets up to Ø 6.4 mm in any material.

PowerBird® Pro **Gold Edition**

The strong one

- for high volumes and fast working sequences!

Thanks to the brushless motor and the 20,000 N setting force the PowerBird® Pro Gold Edition is even more powerful and can even set G-Bulb and PolyGrip® blind rivets up to Ø 6.4 mm in any material.

PowerBird® Pro **Gold Edition with** spring-loaded trigger svstem

The secure one

- the well-proven solution for a reliable gap free riveting process!

For high operating safety and optimal setting results.

TECHNICAL DATA BIRD PRO SERIES

The Bird Pro series deals easily with a wide range of applications and requirements.

Too	I		Material / Ø		Setting force	Power unit	Stroke	Battery	Weight	Equipment	Part no.
AccuBird® Pro		Ø 2.4 up to 5.0 mm Ø up to 6 mm		Ø up to 4.0 mm Ø up to 5,2 mm Ø up to 5.2 mm**	10,000N	Brushless DC motor (BLDC)	25 mm	18 Volt 2.1 Ah	2.0 kg with battery	Nosepieces: 17/24, 17/27, 17/29, 17/32 Maintenance wrench SW12 Sliding battery 18 Volt/2.1 Ah, Charger	143 5447
PowerBird® Pro		Ø 2.4 up to 6.4 mm** Ø up to 8 mm*	Ø up to 6.4 mm	Ø up to 7.7 mm	15,000N	Brushless DC motor (BLDC)	25 mm	18 Volt 2.1 Ah	2.0 kg with battery	Nosepieces: 17/32, 17/36, 17/40, 17/45 Maintenance wrench SW12 Sliding battery 18 Volt/2.1 Ah, Charger	145 0810
PowerBird® Pro Gold Edition		Ø 2.4 up to 6.4 mm Ø up to 8 mm	Ø up to 6.6 mm Ø up to 6.6 mm Ø up to 6.4 mm	Ø up to 7.7 mm	20,000 N	Brushless DC motor (BLDC)	25 mm	18 Vol t 2.1 Ah	2.0 kg with battery	Nosepieces: 17/32, 17/36, 17/40, 17/45 Maintenance wrench SW12 Sliding battery 18 Volt/2.1 Ah, Charger	145 <i>7</i> 636
PowerBird® Pro Gold Edition with spring-loaded trigger sy:	stem	Ø 2.4 up to 6.4 mm Ø up to 8 mm	Ø up to 6.4 mm	Ø up to 7.7 mm	20,000 N	Brushless DC motor (BLDC)	25 mm	18 Volt 2.1 Ah	2.0 kg with battery	Nosepieces: 17/32, 17/36, 17/40, 17/45 Maintenance wrench SW12 Sliding battery 18 Volt/2.1 Ah, Charger	145 7638
	Standard blind ri	ivet	All materials	Alu	Steel/steel						
	MEGA GRIP® BULB-TITE®* G-Bulb PolyGrip®		*except G-Bulb 6.4 **special accessory	Ø					• • • •		



FROM THE CREATOR OF THE BATTERY-POWERED BLIND RIVET SETTING TOOL

The battery-powered riveting tool series for professional and versatile use in trade and industry.

The Bird family

The development of this Bird series for professional use by specialists and industrial users made GESIPA® the inventor of the cable-free and hose-free blind rivet setting technology.

The great success of the maintenance-friendly constructed Bird series is due to the following advantages.

Practical aspects

- Exchange nosepieces and wrench always included in the tool
- Compact, shockproof tool housing
- Spent mandrel evacuation into the mandrel container through backfilling and forwards through the nosepiece by gravity
- Fatigue-free working through well balanced weight repartition and ergonomic grip

Casing and accessories

- Exchange for nosepieces and wrench on the device
- Less frequent emptying due to the large spent mandrel container
- Optimized accessories and special models for many applications

With Li-ion energy

- No memory effect
- High energy yield through high voltage and low weight for easy and fast operation
- Extremely low self discharge
- Battery shape allows the tool to be stored standing on its battery

Mechanics, control system and battery

- Reliable connection of the mechanics and control system
- Cast control system is water and dust-tight
- User-friendly pluggable rechargeable battery







PowerBird® Pow

GFSIPA®

THE BIRD SERIES - INTELLIGENT ENERGY

Lithium-ion technology as mobile power supply for the battery-powered blind rivet setting tools

Li-ion batteries

The GESIPA® battery-powered setting tool AccuBird® is equipped as standard with a 1.3 Ah Li-lon battery. The GESIPA® PowerBird® is supplied with a 2.6 Ah Li-Ion battery. These rechargeable Li-ion batteries feature the Deep Sleep function. To keep intrinsic consumption as low as possible, after a set idle time, the battery automatically assumes "Deep Sleep" mode. The battery can then only be woken in the battery charger and is immediately ready for use.

The powerful 2.6 Ah battery is also optionally available as a special accessory for the AccuBird®. Older tools can of course also be operated with the new Li-lon batteries. Due to the different charging principle used in the Li-lon technology, the charging unit must also be replaced when switching over to Li-lon batteries; the proven charging units for NiCd batteries are however still available.

Charging technology

A special, intelligent circuit in the GESIPA® Li-ion batteries protects against deep discharging, and ensures that the last setting cycle can be completed, before the battery signals its empty condition by switching off. The empty battery is ready for use again after a charging time of only about one hour. The GESIPA® Li-ion charging units are of course also available for the alternating voltages of 110 AC to 230 AC.





The most important advantages of Li-ion technology

- Currently the most efficient mobile power supply

- High energy storage capacity (90-110 Wh/kg)
 Long storage capability due to low self-discharging
- No memory- or lazy-battery effect low mainte-
- nance requirement
 Constant output voltage over the complete dis-
- Large number of **loading cycles**
- Long service life

THE BIRD SERIES

Reliability, high performance, versatility



AccuBird®

The well-proven blind rivet setting tools with Li-lon energy

Developed and produced in Germany since 1992 by the inventor of the battery blind rivet setting tool.

PowerBird®

The well-proven blind rivet setting tool with Li-ion energy and even higher setting performance

The powerful extension of the Bird family from GESIPA® with many capabilities. He is able to cope with almost all structural blind rivets.

PowerBird® Gold Edition

The exclusive Gold edition with 18,000 N setting force

With a setting force of 18,000 N it can even set G-Bulb and PolyGrip® blind rivets up to a diameter of 6.4 mm in all materials.

PowerBird® Solar

Ideal for deep, difficult to access areas in solar applications

Blind rivets from \varnothing 4.8 mm steel up to 6.4 mm all materials with a setting force of 14,000 N. The ideal tool for the safe handling of SolarGrip® special rivets thanks to the standard extension unit and the optional spring-loaded trigger

TECHNICAL DATA BIRD SERIES

The Bird series deals easily with a wide range of applications and requirements.

Tool	Material / Ø	Setting force	Power unit	Stroke	Battery	Weight	Equipment	Part no.
AccuBird®	Ø 2.4 up to 5.0 mm Ø up to 4.8 mm Ø up to 4.0 mm Ø up to 6 mm Ø up to 5.2 mm Ø up to 5.2 mm**	10,000N	DC motor	20 mm	14.4 Volt 1.3 Ah	2.0 kg with battery	Nosepieces: 17/24, 17/27, 17/29, 17/32 Maintenance wrench SW12 Battery 14.4 Volt/2.6 Ah, Charger	143 4898
PowerBird®	Ø 2.4 up to 6.4 mm Ø up to 6.4 mm Ø up to 7.7 mm at 7.7 mm**	14,000N	DC motor	20 mm	14.4 Volt 2.6 Ah	2.2 kg with battery	Nosepieces: 17/32, 17/36, 17/40, 17/45 Maintenance wrench SW12 Battery 14.4 Volt/2.6 Ah, Charger	145 <i>7</i> 186
PowerBird® Gold Edition	Ø 2.4 up to 6.4 mm Ø up to 6.6 mm Ø up to 7.7 mm at 7.7 mm** Ø up to 6.6 mm Ø up to 6.4 mm	18,000N	DC motor	20 mm	14.4 Volt 2.6 Ah	2.2 kg with battery	Nosepieces: 17/32, 17/36, 17/40, 17/45 Maintenance wrench SW12 Battery 14.4 Volt/2.6 Ah, Charger	145 <i>7</i> 179
PowerBird® Solar	Ø 2.4 up to 6.4 mm* Ø up to 6.4 mm	14,000N	DC motor	20 mm	14.4 Volt 2.6 Ah	2.4 kg with battery	Nosepieces: 17/32, 17/36, 17/40, 17/45, 17/48 BT two batteries 14.4 Volt/2.6 Ah, Charger approx. 167 mm extension unit	145 <i>7</i> 191
Standard blind rive MEGA GRIP® BULB-TITE® G-Bulb PolyGrip®	***special accessory required							

ACCESSORIES FOR THE BIRD SERIES/BIRD PRO SERIES

The wide range of accessories allows the tool to be adapted to deal with almost any challenge. Whether in trade, in the construction industry or in industrial applications.

Extension units

Allows easy access to rivet sites which are difficult to access



1) The extension units are used for riveting sites which are situated low down or are difficult to access.

The **one-piece extension** units replace steel head sleeves, are extremely slim and therefore particularly suitable where space is restricted. One-piece extension units are offered in different sizes for all tools.

The extension unit consists of three parts: the steel head sleeve, the jaw pusher and the adapter. The total length equals the length from the steel sleeve plus the standard nosepiece.

(2) The multi-piece extension units are screwed in between the tool and the existing steel sleeve. The total length equals the length of the steel sleeve plus the extension. The multi-piece extension units allow the steel sleeve to be extended variably in 100 mm stages.

Retaining nosepiece

Working even in vertical position without difficulties



Thanks to the retaining nosepiece the inserted rivet stays in any position due to elasticity. Even in vertical riveting processes the rivet is held securely in the tool.

Retaining nosepieces are available in different sizes for all tools except PowerBird® Solar.

Spring-loaded trigger system

For gap-free riveting of components



The spring-loaded trigger system ensures that the parts to be riveted reliably make contact without any gaps before riveting. Furthermore, the operator will be certain that the blind rivet has reached its end position in the hole before setting and the setting head is in contact with the material. The pressing force can be varied with springs depending on the application.

The spring-loaded trigger system is available for AccuBird®, PowerBird® Pro, PowerBird® Pro and PowerBird® Pro Gold Edition on request.

Transparent spent mandrel container

Residual mandrels always controlable



The classic spent mandrel container of the Bird Pro series is also available in a transparent version. This allows you to keep an eye on the amount of spent mandrels.

Extension for spent mandrel container



Fitting for AccuBird® and PowerBird® as well as for the Bird Pro series in two different sizes – working longer, less frequent emptying.

Universal nosepiece for AccuBird®



The universal nosepiece replaces up to five nosepiece sizes. The integrated rotary star in the steel sleeve can be unlocked easily without tools in order to select the appropriate size of nosepiece.

This helps saving time when riveting different blind rivet sizes.

Angle head 90° compact for AccuBird® and PowerBird® Angle head 90° compact for the Bird Pro series

High setting force and easy access in tight installation areas



The angle head 90° compact and the angle head 90° are designed for use in very narrow and confined spaces. The rugged design makes it possible to set blind rivets with a high setting force even in working areas that are difficult to access. They can be positioned freely in every position (360°) on the tensile axis.

The angle head 90° compact can set standard blind rivets with a setting force up to 10 kN, the angle head 90° can set standard blind rivets with a setting force up to 20 kN.





ACCESSORIES BIRD SERIES

Accessories	Picture	AccuBird®	PowerBird®	PowerBird® Gold Edition	PowerBird® Solar			
Jaws (spare parts)	380	143 4958	143 4104	143 4104	143 4173			
Battery 1.4 V/1.3 Ah (Li-lon)		143 4921	145 7269	145 7269	145 7269			
Power battery 1.4 V/2.6 Ah (Li-lon)	LE STA	143 4921	143 4921	143 4921	143 4921			
Charger for 14.4 V Li-lon battery		145 7282	145 7282	145 7282	145 7282			
Extension unit 50 mm (single-piece)		145 7273	145 7214	145 7214	-			
Extension unit 100 mm (single-piece)		145 7274	145 7215	145 7215	-			
Extension unit 150 mm (single-piece)		145 0622	146 4038	146 4038	-			
Extension unit (multi-piece per 100 mm)	11	145 7318	145 7229	145 7229	-			
Extension for spent mandrel container	•	143 5034	143 5034	-	-			
Angle head 90° compact		145 7252	145 7252	+	-			
Universal nosepiece	1	143 4960	-	-	-			
Nosepiece	Nosepiece See chart nosepieces on page 18/19							
Retaining nosepiece	g nosepiece See chart nosepieces on page 18/19							

ACCESSORIES BIRD PRO SERIES

Accessories	Picture	AccuBird® Pro	PowerBird® Pro	PowerBird® Pro Gold Edition	PowerBird® Pro Gold Edition with spring-loaded trigger system		
Jaws (spare parts)	380	143 5568	143 5568	143 5568	143 5568		
Sliding battery 18.0 V/2.1 Ah (Li-lon)		145 7641	145 7641	145 7641	145 7641		
Charger for 18.0 V Li-lon battery		145 7642	145 7642	145 7642	145 7642		
Transparent spent mandrel container		145 0837	145 0837	145 0837	145 0837		
Extended spent mandrel container 30mm 60mm	00	145 0838 145 0839	145 0838 145 0839	145 0838 145 0839	145 0838 145 0839		
Extension unit +35 mm (single-piece)		145 0860	145 7650	145 7650	-		
Extension unit +85 mm (single-piece)		145 0861	145 7651	145 7651	-		
Extension unit +135 mm (single-piece)		145 0862	145 0823	145 0823	-		
Extension unit +50 mm (single-piece)		-	-	-	145 0821		
Extension unit +100 mm (single-piece)		-	+	-	145 0822		
Extension unit (multi-piece, per 100 mm)	11	145 0859	145 0820	145 0820	-		
Angle head 90°		146 4882	146 4882	146 4882	-		
Nosepiece		See chart nosepieces on page 18/19					
Retaining nosepiece		See chart nosepieces on page 18/19					

NOSEPIECES FOR BLIND RIVET SETTING TOOL

AccuBird®, AccuBird® Pro

Blind rivet	Blind rivet Ø in mm	Material	approx. pc/battery charge		Nosepiece	Part no.
			AccuBird® Pro	AccuBird®		
	2.4	Alu	1,800	1,500	17/18	143 4976
	3.2	CAP®-Alu, CAP®-Cu	1,300	1,000	17/18	143 4976
	3 & 3.2	Alu	1,100	800	17/24	143 4955
	3 & 3.2	Steel	1,100	800	17/24	143 4955
	3 & 3.2	Stainless steel	1,100	800	17/24	143 4955
Standard	4.0	Alu	1,100	800	17/24	143 4955
Standara	4.0	Steel	1,100	700	17/27	143 4973
	4.0	Stainless steel	940	640	17/29	143 4974
	4.8 & 5	Alu	850	550	17/29	143 4974
	4.8 & 5	Steel	720	420	17/32	143 4975
	4.8 & 5	Stainless steel	550	320	17/36	143 4977
	6	Alu	400	240	17/36	143 4977
	4.0	Alu	1,300	1,000	17/26 BT	143 4985
	5.2	Alu	1,100	800	17/32 BT	143 4986
BULB-TITE®	6.3	Alu	800	600	17/42 BT	143 4988
	6.4	Steel	550	300	17/42 BT	143 4988

Tool	Retaining nosepiece	Part no.
	17/18 R	143 5010
AccuBird®, AccuBird® Pro	17/24 R	143 5011
Accobile , Accobile F10	17/27 R	143 5012
	17/29 R	143 5013

NOSEPIECES FOR BLIND RIVET SETTING TOOL

PowerBird[®], PowerBird[®] Gold Edition, PowerBird[®] Pro Gold Edition

Blind	Blind rivet	Material	app	prox. pc/ba	ittery char	ge	Nosepiece	Part no.
rivet	Ø in mm		PowerBird® Pro	PowerBird® Pro Gold Edition	PowerBird®	PowerBird® Gold Edition		
	4.8 & 5.0	Steel, alu	1,000	1,800	700	700	17/32	143 4975
	4.8 & 5.0	Stainless steel	700	1.600	890	890	17/36	143 4977
	6.0	Alu	650	1.000	560	560	17/36	143 4977
Standard	6.0	Steel	500	650	300	300	17/40	143 4999
	6.4	Alu, PG-Alu	550	600	420	420	17/45	143 4860
	6.4	Steel	450	530	250	250	17/45	143 4860
	8	Alu	500	510	350	350	17/45	143 4860
	4.0	Alu	1,200	1,300	1,000	1,000	17/26 BT	143 4985
	5.2	Alu	1,000	1,200	900	900	17/32 BT	143 4986
BULB-TITE®	6.3	Alu	800	800	590	590	17/42 BT	143 4988
BOLB-IIIE	6.3	Steel	700	550	310	310	17/42 BT	143 4988
	6.3	Monel	650	600	380	380	17/42 BT	143 4988
	7.7	Alu	700	680	470	470	17/48 BT	143 4989
	4.8	Alu	800	970	600	600	17/31 MG	143 4993
	6.4	Alu	750	940	420	420	17/41 MG	143 4865
MEGA GRIP®	4.8	Steel	750	920	420	420	17/31 MG	143 4993
	6.4	Steel	300	230	150	150	17/41 MG	143 4865
	4.8	Stainless steel	700	900	420	420	17/31 MG	143 4993
	6.4	Stainless steel	250	230	150	150	17/41 MG	143 4865

Tool	Retaining nosepiece	Part no.
PowerBird®	17/32 R	143 5014
PowerBird® Gold Edition	17/36 R	143 5015
PowerBird® Pro	17/40 R	145 7347
PowerBird® Pro Gold Edition	17/45 R	145 7348

GESIPA Blindniettechnik GmbH Nordendstraße 13–39 64546 Mörfelden-Walldorf T +49 6105 962 0 info@gesipa.com www.gesipa.com

