



22-44 PRO-3 DRUM SANDER with Digital Read Out

FEATURING:

**SAND
SMART™**

*Variable Feed
control produces
the ultimate finish*



Digital Read Out



The new JET model 22-44 PRO-3 - Drum Sander has even more great features. We've added a digital readout that displays the exact thickness of the finished piece or allows the user to preset the exact thickness they want for the finished piece. Four casters mobilize your drum sander and also lock into place for stability during use. Both infeed and outfeed tables come standard with the 22-44 PRO-3 and provide extra support for the workpiece. The powerful 3HP motor is designed for heavier use for longer periods of time.

jettools.com



22-44 PRO-3 DRUM SANDER with Digital Read Out



Digital Read Out



Variable Feed
control produces the
ultimate finish



A. DRO

B. SANDSMART™ Variable Feed/
Speed

C. 3HP Continuous-Duty Motor

D. Self Cooling 22" 2-Pass
Capacity Drum

E. Truss-like Carriage Arm

F. Casters

G. Infeed/Outfeed Tables

FEATURES


- Our EXCLUSIVE SandSmart™ infinitely variable-feed control produces the ultimate finish at a rate from 0 to 10 feet per minute and prevents machine overload
- Digital read-out for more accurate sanding
- Patented conveyor belt TRACKERS™ dramatically reduce the need for manual belt adjustments
- 22" wide suspended drum is supported on both ends with a truss-like carriage arm for greater strength and easy alignment to the table surface for consistent performance
- Sealed and permanently lubricated drum ball bearings for longer life
- Precision-flattened reinforced steel conveyor bed and no-give power feed belt provide a constant smooth sanding action for better results
- Adjustable drum height and downward pressure feature virtually eliminates snipe
- Large cast-iron handwheel adjusts height at 3/32" per turn for precise sanding thickness control
- Patented abrasive take-up fasteners make changing abrasives quick and easy
- Depth gauge has locking stop to ensure accuracy
- On/off switch with overload protection is front-mounted for operator's convenience
- One feed and one drive motor for superior sanding control
- Continuous-duty, 3HP motor is designed for heavier use for longer periods of time

SPECIFICATIONS

Stock Number	649600
Model Number	22-44 PRO
Style	Open Stand
Max. Board Width (in.)	44 (2 passes)
Max. Board Thickness (in.)	4
Min. Board Length (in.)	2-1/4
Min. Board Thickness (in.)	1/32
Drum Diameter (in.)	5
Drum Length (in.)	22
Drum Speed (RPM)	1600
Conveyor Speed (SFPM)	1 to 10
Conveyor Motor	43 in.-lbs. torque, direct drive, dc
Dust Port Diameter (OD/in.)	4
Amps	8
Motor HP	3HP
Motor Phase	1Ph
Motor Voltage	230V
Prewired	230V
Net Weight (lbs.)	402

ACCESSORIES

Infeed/Outfeed Tables, 10"Dx24"W	98-2201
Caster Set - Box of (4) 20-0622	98-0130
Tuf Tool	98-0060
22-44, 36 Grit, 3-Wraps in Box	60-2036
22-44, 60 Grit, 3-Wraps in Box	60-2060
22-44, 80 Grit, 3-Wraps in Box	60-2080
22-44, 100 Grit, 3-Wraps in Box	60-2100
22-44, 120 Grit, 3-Wraps in Box	60-2120
22-44, 150 Grit, 3-Wraps in Box	60-2150
22-44, 180 Grit, 3-Wraps in Box	60-2180
22-44, 220 Grit, 3-Wraps in Box	60-2220
22-44, 36,80,120 Grit, 1 of Each Wrap in Box	60-2000



98-2201



98-0130



98-0060

jettools.com