

3/8" and 1/2" Impacttools™ and Ratchets



Model*	Description	Handle	Free Speed rpm	Max Torque ft-lb (Nm)	Recommended Torque Range ft-lb (Nm)	Weight lb (kg)	Length in (mm)	cfm	Recommended Hose Size in (mm)
3/8" RATCHETS									
107XPA	3/8" square	Lever	160	54 (73)	10 – 45 (14 – 61)	2.75 (1.25)	11" (279)	19	3/8" (10)
109XPA	3/8" square	Lever	220	76 (95)	10 – 60 (14 – 81)	3.3 (1.4)	12" (302)	24	3/8" (10)
IMPACTTOOLS									
3/8" HEAVY-DUTY									
1702P1	3/8" square	Pistol	10,000	125 (170)	20 – 100 (27 – 136)	2.75 (1.25)	5.5" (140)	15	5/16" (8)
3/8" MAINTENANCE-DUTY									
2115PTiMAX	3/8" square reverse bias	Pistol	15,000	F: 250 (339) R: 300 (407)	25 – 230 (34 – 312)	2.49 (1.13)	5.95" (151)	17	3/8" (10)
2115TiMAX	3/8" square reverse bias	Pistol	15,000	F: 250 (339) R: 300 (407)	25 – 230 (34 – 312)	2.48 (1.12)	5.95" (151)	17	3/8" (10)
212	3/8" square	Pistol	10,000	180 (244)	20 – 150 (27 – 204)	2.89 (1.31)	6" (152)	11	3/8" (10)
1/2" MAINTENANCE-DUTY									
2135PTiMAX	1/2" square reverse bias	Pistol	9,800	F: 600 (813) R: 780 (1054)	50 – 550 (68 – 746)	3.95 (1.79)	7.35" (187)	24	3/8" (10)
2135TiMAX	1/2" square reverse bias	Pistol	9,800	F: 600 (813) R: 780 (1054)	50 – 550 (68 – 746)	3.95 (1.79)	7.35" (187)	24	3/8" (10)
2135Ti-2MAX	1/2" square 2" extended anvil	Pistol	9,800	F: 600 (813) R: 780 (1054)	50 – 550 (68 – 746)	4.4 (2)	9.47" (241)	24	3/8" (10)
2135QTiMAX	1/2" square Quiet tool	Pistol	9,800	F: 600 (813) R: 780 (1054)	50 – 550 (68 – 746)	4.05 (1.84)	7.35" (187)	24	3/8" (10)
2135QPTiMAX	1/2" square Quiet tool	Pistol	9,800	F: 600 (813) R: 780 (1054)	50 – 550 (68 – 746)	4.05 (1.84)	7.35" (187)	24	3/8" (10)
231HA-2	1/2" square 2" extended anvil	Pistol	8,000	590 (800)	25 – 350 (34 – 475)	6.1 (2.76)	9.13" (236)	22	3/8" (10)
231C	1/2" square	Pistol	8,000	600 (813)	25 – 350 (34 – 475)	5.8 (2.63)	7.3" (185)	22	3/8" (10)
232TGSL	1/2" square	Pistol	10,000	625 (847)	40 – 400 (54 – 544)	6 (2.72)	7.3" (185)	23	3/8" (10)

*P denotes a pin-type socket retainer in drive sizes 3/8" – 1/2" and a through-hole socket retainer in drive sizes 3/4" and above.