



1791230K : 64B TABLE SAW, 1.75 HP 115/230V, 50" FENCE WITH RIVING KNIFE



The 64B table saw, with left tilt arbor, offers 1-3/4 horsepower in dual voltage to meet the demands of the professional contractor. The transparent blade guard has independent leaves, and the quick release riving knife reduces chance of kickback. A low profile riving knife is included for non-through cuts. An arbor lock is accessed from above the table, eliminating the need for dual blade wrenches. The T-slot miter gauge has rack-and-pinion angle setting, positive stops, and extension plate for expanded workpiece support. The 64B has cast iron table and wings with front edge bevel, and the working area is further expanded by the melamine-surfaced wood extension table. The exclusive Accu-Fence® system is available in 30" or 50" rip cut capacity. Storage hooks on the stand keep your accessories within reach.

Features and Benefits

- Riving knife maintains close blade proximity to reduce chance of kickback
- Micro-adjust miter gauge with extension plate offers wider crosscut support
- Blade guard and riving knife have quick release for tool-less mounting and removal
- Precision ground cast iron table and wings have beveled edge for smooth miter gauge entry
- Built-in extraction port increases dust collection efficiency
- Heavy cast iron trunnion ensures smooth blade positioning
- Chrome trimmed handwheels are ergonomically designed
- Accu-Fence locks to rail without play
- (Blade not included)

Accessories

- 1791088 Dado Insert, 64B
- 2195075Z Fence Assembly for PM64B
- 2653045Z 30" Rail Set for PM64B
- 2653046Z 50" Rail Set for PM64B
- 6441000Z LEG ASSEMBLY
- 6827036 WOOD EXT. TABLE, 27 X 17, for 64A, 64B
- 708118 JMB-UMB UNIVERSAL MOBILE BASE
- 708158 MOBILE BASE EXTENSION KIT
- 708295 JTG-10Q TENONG JIG W/QCK RLSE



1791230K : 64B TABLE SAW, 1.75 HP 115/230V, 50" FENCE WITH RIVING KNIFE

Specification	Value	
Style (Type)	Contractor	
Blade Diameter (In.)	10	
Arbor Diameter (In.)	5/8	
Arbor Speed (RPM)	4,000	
Maximum Depth of Cut (In.)	3-1/8	
Maximum Depth of Cut at 45 Degrees (In.)	3-1/8	
Maximum Rip Left of Blade (In.)	12	
Maximum Rip Right of Blade (In.)	50	
Table in Front of Saw Blade at Maximum Depth of Cut (In.)	11-1/2	
Maximum Diameter of Dado (In.)	8	
Maximum Width of Dado (In.)	13/16	
Table Type	cast iron	
Table Height from Floor (In.)	36	
Table Size (In.)	44-1/4 x 27	
Dust Collection Minimum CFM Required (CFM)	350	
Motor Power (HP)	1-3/4	
Motor Phase	1	
Motor Voltage (V.)	115, 230	
Prewired Voltage (V.)	115	
Motor Current (Amps)	15, 7-1/2	