

shield

Static Dissipative Products

FG-7000 SERIES FOOT GROUNDERS

New Product

**If you're seeing too much static
Put yourself in our foot grounders!**

Description

The Ohm-Stat® FG-7000 Series foot grounders establish a continuous ground path between mobile personnel and static dissipative flooring, floor finish or paint. Did you know that electrostatic voltages can reach as high as 35,000 volts if mobile personnel are ungrounded? Using the Ohm-Stat® FG-7000 Series foot grounders this dissipation drops to zero volts in less than 0.1 seconds in all humidities.



The Ohm-Stat® FG-7000 Series foot grounder is comprised of a conductive reinforced rubber foot cup, elastic hook and loop, or D-ring, and a conductive nylon grounding tab. This functional design fits a wide variety of men's and women's shoes, boots, safety shoes, loafers, tennis shoes and running shoes.

To ensure that the grounding is continuous a foot grounder must be worn on both shoes. Any conductive floor surface can be used in conjunction with the foot grounder particularly suitable are the Static Solutions, Inc Ohm-Shield® floor finish, floor paint and Ohm-Stat® floor mats.

Property

- INSTANT STATIC DISSIPATION
- FITS ALL SHOES
- DURABLE, LONG LIFE, WASHABLE
- GROUNDS MOBILE PERSONNEL
- MATERIALS MEET EOS-CECC SPECIFICATIONS
- RED HOOK-LOOP MATERIAL AVAILABLE
- TWO LAYER INTERIOR-NON BLACK
- D-RING AND ELASTICIZED HOOK AND LOOP DESIGN
- ONE MEGOHM RESISTOR
- INDUSTRIAL TIRE GRADE CROSSLINKED RUBBER

Benefit

- PROVEN EFFECTIVE
- VERSATILE
- PROVEN TOUGH
- PRODUCT PROTECTION
- QUALITY
- VISIBLE FOR SUPERVISOR
- PROTECTS SHOE FROM BLACK MARKING
- COMFORTABLE, PERSONAL PREFERENCE
- SAFETY DESIGN
- LONGEVITY, HIGH ABRASION AND TEAR RESISTANCE



INSTRUCTIONS

1. Position the heel of shoe inside rubber cup with D-ring or hook and loop on either side of ankle.
 2. Fasten elastic loop, material over top of hook material or insert hook and loop through D-ring.
 3. Insert tab inside of shoe or inside of stocking for intimate contact.
 4. Test shoe grounder at the heel grounder tester to ensure proper conductivity, such as the CT-8900 test station available from Static Solutions, Inc.
- Can be washed with soap and water in order to remove dirt and contamination which can adversely affect its static dissipative properties.

**Check out our full catalog at
www.staticsolutions.com**

Warranty: Static Solutions, Inc. expressly warrants that for a period of (1) one year from the date of purchase any Static Solutions, Inc. product will be free of defects in materials and will function within its specifications. Within the warranty period, the product will be repaired or replaced at Static Solutions, Inc.'s option with no cost to the customer as long as Static Solutions, Inc. receives notice during the warranty period. Defective products must be shipped prepaid to Static Solutions, Inc.'s factory. Call Static Solutions, Inc.'s customer service at 508-480-0700 for a return authorization number. Include a copy of the invoice, packing slip, or other proof of purchase.

Warranty Exclusion: The foregoing express warranty is made in lieu of other product warranties express and implied, including merchantability and fitness for a particular purpose which are specifically or indirectly disclaimed. The express warranty will not apply to defects or damage due to neglect, misuse, accidents, alterations, operator error, failure to properly maintain, follow instruction, or failure to clean or repair products.

Limit of Warranty: In no event will Static Solutions, Inc. or seller be responsible or liable for special, incidental or consequential losses or damages, whether based on tort, contract, or the use of or inability to use, the product. Before using the product users shall determine the suitability of the product for their intended use. The users assume all risk and liability whatsoever in connection therewith. Fulfillment of Static Solutions, Inc.'s warranty obligations will be the customer's exclusive remedy and Static Solutions, Inc. and seller's limit of liability for any breach of warranty or otherwise.

DISTRIBUTED BY:

Other Products

- Resistivity Meters
- Mats
- Combo Meters
- Wrist Straps
- Floor Finish
- Paint
- Clean Room Products

*For additional OHM-STAT product literature, call or fax
the Static Solutions, Inc. sales department.*



Static Solutions, Inc.

43 Broad Street, Hudson MA, 01749
Tel: 978.310.7251 Fax: 978.310.7146
Visit our website: www.staticsolutions.com