




Heavy Duty 2™

Designed to easily automate your new and existing machinery, giving you repeatable accuracy in any pushing, pulling or positioning application.



Heavy duty automated feed system for positioning material up to 2100 lbs (952 Kg)

This is the big boy

Heavy Duty 2^{TM} , big brother to the Tiger-Stop® and TigerTurbo TM , offers higher maximum load capacity.

For your heavy loads, get heavy duty power! The $HD2^{TM}$ offers 2100 lbs (952 Kg) of pushing capacity. When no other machine can push it, pull it, or position it, $HD2^{TM}$'s rack and pinion drive get's the job done.





Accuracy .008 Inches .20 mm
Capacity 2100

952 Kg

32.9 Meters

Max Length 108

Heavy Duty 2[™] Specifications

Repeatable Accuracy
.008 in (.20 mm)

Accuracy Validation
NIST Certified

Power Requirement
208 Vac @ 15 Amps
50/60 Hz 1Ph Isolated Circuit
Drive Type
Rack & Pinion

Working Lengths
12 - 108 feet (3.6 - 33 meters)

Motor Type
AC servo w/optical encoder

Pushing Capacity
490 lbs (222 kg) - w/o rollers
2100 lbs (952 Kg) w/ rollers
Warranty
1 Year Bumper to Bumper









RoHS Compliant





Upgrade to Dynamic Optimization and Downloading





PC,PLC or barcode control interface



Dynamic Optimization $^{\text{TM}}$ for material yield & defect optimization. Get high quality parts from lower grades of lumber.








Heavy Duty 2 has an accessory for any application.

Comparison Chart

What TigerStop is right for you?





TigerStop LLC 12909 NE 95th Street Vancouver, WA 98682