

1/4" Hex Drive Nutsetters

6 Point, Bolt Clearance



Part Number 6 Point	Size In.	Overall Length In.	Socket Nose Diameter In.	Depth of Clearance (A) In.
6B-0808•	1/4	3 1/4	7/16	1 3/8
6B-0809•	9/32	3 1/4	1/2	1 3/8
6B-0810•	5/16	3 1/4	1/2	1 3/8
6B-0811•	11/32	3 1/4	9/16	1 3/8
6B-0812•	3/8	3 1/4	9/16	1 3/8
6B-0814•	7/16	3 1/4	21/32	1 3/8
6B-0816•	1/2	3 1/4	3/4	1 3/8
6B-0818•	9/16	3 1/4	13/16	1 3/8
6B-0820•	5/8	3 1/4	7/8	1 3/8

See bolt clearance Tool Tip page 32.

7/16" Hex Drive Nutsetters

6 Point



Part Number 6 Point	Size In.	Overall Length In.	Socket Nose Diameter In.
6N-1410-3	5/16	3	9/16
6N-1412-3	3/8	3	9/16
6N-1414-3	7/16	3	3/4
6N-1416-3	1/2	3	13/16
6N-1416-4	1/2	4	13/16
6N-1418-3•	9/16	3	7/8
6N-1418-6	9/16	6	7/8
6N-1420-3	5/8	3	1
6N-1424-3	3/4	3	1 1/8
6N-1424-6	3/4	6	1 1/8

5/8" Hex Drive Nutsetters

6 Point



Part Number 6 Point	Size In.	Overall Length In.	Socket Nose Diameter In.
6N-2028-4	7/8	4	1 3/8
6N-2036-4	1 1/8	4	1 5/8

Hand Drivers

Drivers with Self-Contained Insert Bits



Part No.	Female Hex Size	Overall Length In. mm	Blade Projection In. mm
M-15-SC	1/4	8 1/2 216	4 3/8 111
Phillips #1, #2, #3; Slotted 4F-5R, 10F-12R; hollow handle.			
M-15-SC-A•	1/4	8 1/2 216	4 3/8 111
Without bits; hollow handle.			

Replaceable Bit Drivers



Part No.	Female Hex Size	Overall Length In. mm	Blade Projection In. mm
1510-P•	1/4	2 3/4 70	7/8 22
1500-P•	1/4	7 1/2 191	3 9/32 83

Replaceable Bit Drivers – Magnetic



Part No.	Female Hex Size	Overall Length In. mm	Blade Projection In. mm
M-1505-P•	1/4	2 3/8 60	3/8 10
M-1500-P•	1/4	8 1/2 216	4 3/8 111

Industrial Bit Kit



24 Bit Kit•

Tool kit includes plastic carrying case with:
Magnetic hand driver and magnetic bit holder.
Phillips bits: #1, #2, #3
Slotted bits: 3F-4R, 4F-5R, 6F-8R, 8F-10R, 10F-12R
Torx® bits: T-10, T-15, T-20, T-25, T-27, T-30, T-40
Square Recess bits: 3/32", 1/8"
Hex bits: 5/64", 3/32", 7/64", 1/8", 9/64"
Pozidriv® bits: #1, #2

Awls



Part Number	Overall Length In. mm	Shank Diameter In. mm
AW-95•	7 7/16 189	.307 7.8
AW-95-L•	8 203	.307 7.8
AW-95-LL•	8 7/8 225	.307 7.8

Use awls to line up holes and scratch mark surfaces.

• Indicates a commonly requested item that is either in stock or has a max typical leadtime of 4 weeks from the factory. No minimum on these items.

Pozidriv® is a registered trademark of the Phillips Screw Co. Torx® is a registered trademark of the Camcar Division of Textron.